

PETER'S PERFECT WATER RECIPE

for the Nature 2 System

Remove the filter(s), and fill the spa through the filter hole to the fill line on the weir gate, or approximately two or three inches above the filter(s).

Turn on the power at the service disconnect, or at the main breaker. There will be a short delay and then the tub will come on. Turn on the jets and verify that there is sufficient water flow.

- Set the temperature.
- Set the filter cycle to 12 hours of filtration for every 24 hours period.
(Set Dream Maker filter cycle to F0.)
- Test the water with a test strip, and adjust pH. (Using **Spa Up**, or **Spa Down**.)
- Adjust. Total Alkalinity. (Using **Alkalinity Increaser** or **Spa Down**.)
- Adjust Total Hardness. (Using **Calcium Booster**.)

Install the **Nature 2 Cartridge**. (The cartridge is good for four months, and **must be replaced every four months** along with fresh clean water.)

Add one tablespoon of **Spa 56** to activate the new **Nature 2 Cartridge**.

After Each Use: Add one tablespoon of **Renew Shock**.

WEEKLY:

- Monday** Test water & adjust pH and Alkalinity.
(Using **Spa Up**, or **Spa Down** and **Alkalinity Increaser**.)
Add one ounce of **Bright and Clear**.
Add one ounce of **Spa Perfect**.
- Wednesday** Add one ounce of **Spa Defender**.
- Friday** Add one tablespoon of **Spa 56**, and one capful of **Renew Shock**.
Run the jets on high for 30 minutes with the cover off the spa.

MONTHLY: Soak filters in **Filter Cleaner** for at least three hours, or overnight.

SANITIZING

Nature 2 Cartridge
Renew Shock
Spa 56

MAINTENANCE

Bright and Clear
Spa Defender
Spa Perfect
Cartridge Filter Cleaner
Filter Cleaner

ADJUSTING

Spa Up
Spa Down
Alkalinity Increaser
Calcium Booster
Test Strips